



DIMENSIONS

TECHNICAL SPECIFICATIONS

| Idl |
|-----|
| sys |
| W0 |
| two |
| ma |
| ma |
| ser |
| im |
| fre |
| din |
| we |
| we |
| cor |
| col |
| fea |
| |
| |
| |

| range | <50m ² |
|-----------------------|-------------------|
| system | full range driver |
| woofer | 6" paper cone |
| tweeter | - |
| max power (100V) | 3 - 6 - 9W |
| max power (8Ω) | - |
| sensitivity (1W / 1m) | 91dB |
| impedance | - |
| frequence range | 80Hz - 18kHz |
| dimensions (Ø x d) | 170mm |
| weight / piece | 200 x 80mm |
| weight / piece | 0,9kg |
| composition | ABS |
| colour | white |
| features | spring clip |
| | |
| | |
| | |

MDT600-P

The MDT600-P is the most widely used inwall speaker in 100V projects. Its large 6" driver guarantees a warm sound.



The larger the diameter of the driver, the bigger the suppression of the speaker. As a result, the speaker is easily able to fill corridors, canteens, offices or reception areas, such as here.

 \odot

artsound

 ■ artsoundaudio

 ■ info@artsound.be

 (\mathbf{f}) ArtSound.Audio

www.artsound.be