



COLOURS white / black / quartz



TECHNICAL SPECIFICATIONS





power selector



plug-in screw adaptor

range	<40m²
system	2-way
woofer	3,5" polypropylen mica cone
tweeter	1/2" PEI Ferrite
bass reflex	yes
magnetic shielded	no
max. power (100V)	2 - 4 - 8 - 15W
max. power (8Ω)	50W / 8Ω
sensibility (1W / 1m)	90dB
frequency range	100Hz - 20kHz
dimensions (h x w x d)	180 x 115 x 112mm
weight / piece	1,2kg
composition	ABS
colour	white / black / quartz
suspension	u-wall bracket (incl.)

UNI30T

Universals. The name gives the game away: they can be used anywhere! Not only in terms of location, but sound too. Thanks to the timeless design, the Universals embodies a striking neutrality. On the other hand, with respect to performance, it's quite dominant: warm, detailed and with a wide reach thanks to ArtSound sound technology. This T-version is fitted with a transformer, allowing different units into one circuit. The unit is dust- and moisture-resistant. The plug-in screw terminal facilitates easy connection of the speaker cable.



You'll find the UNI30 at Starbucks, but also offices. refrigeration areas, conference rooms, warehouses, stations, etc.





⁽f) ArtSound.Audio



