

DIGITUS CAT 6A S/FTP patch cord

DK-1644-A-300
EAN 4016032327851



CAT 6A S-FTP patch cord, Cu, LSZH AWG 26/7, length 30 m, color grey

The DIGITUS® Category 6A Class EA patch cords are manufactured and tested to the ISO/IEC 11801 and DIN EN 50173 Category 6 A specifications. They will guarantee the installed cabling system is compliant with the ISO & EN channel specification requirements and will provide optimum performance levels of DIGITUS® Category 6A cabling. The performance is tested up to 500 MHz inclusive performance characteristics such as near end cross talk ("NEXT"). DIGITUS® patch cords are designed and produced to fulfill the highest requirements of various application areas in full volume. Each cable is fitted with a molded boot which comes with kink protection and strain relief. Furthermore the boot is equipped with a latch protection that prevents the latching lever against breaking. You can easily identify the Category 6A, because of the transparent yellow colored connector.

Future-oriented standards and high-end quality for your network

- 2x RJ45 (8P8C) connectors
- Boots with kink protection, strain relief and latch protection
- Length marking on boot
- Conductor: Copper (Cu)
- Assortment: Twisted Pair Patch Cables
- Slim Version: no
- Length: 30 m
- Connector 1: Modular RJ45 (8/8) plug
- Connector 2: Modular RJ45 (8/8) plug
- Category: CAT 6A
- Color: grey
- Configuration: 1:1
- Jacket: LSOH
- Shielding: S-FTP, pairs in metal foil and braid shielding
- Structure: 4 x 2 AWG 26/7, twisted pair

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	12	12.24	36.00	36.00	27.00	34,992.00
Packaging Unit Inside	1	1.02	19.00	19.00	7.00	2,527.00
Packaging Unit Single	1	1.02	4.60	28.00	39.00	5,023.20
Net single without Packaging	1	0.96	3,000.00	1.20	1.30	0.00

More images:



