

DIGITUS CAT 6A modular couplers, shielded

DN-93905
 EAN 4016032291824



CAT6A modular coupler, full shielded RJ45 to RJ45

Corresponds with requirements channel performance Class EA ISO/IEC 11801 for up to 500 MHz

- 2 x RJ-45 female
- Assignment: 1:1
- Shielded version

- Material enclosure: Brass sheet - shining Nickel plated
- Material PCB: FR4, 1.2 mm thickness
- Material contacts: Phosphor bronze
- Contacts coating: Nickel, gold plated 0.6 μ
- Mating cycles: ≥ 750
- Operating temperature: -10 °C ~+50 °C

| Logistics | | | | | | |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³ |
| Packaging Unit Carton | 500 | 10.10 | 54.50 | 34.50 | 13.50 | 25,383.40 |
| Packaging Unit Inside | 50 | 1.01 | 25.00 | 23.00 | 7.00 | 4,025.00 |
| Packaging Unit Single | 1 | 0.02 | 2.00 | 7.00 | 12.00 | 168.00 |
| Net single without Packaging | 1 | 0.01 | 1.50 | 2.50 | 4.00 | 0.00 |

More images:

