

General	
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Humidity	20% to 90%, non-condensing
Power Consumption	2.5W

Technical	
HDMI Compliance	HDMI 2.0
HDCP Compliance	HDCP 2.2 / 1.4
Video Bandwidth	18 Gbps
Video Resolution	4K2K@60Hz, 4K2K@30Hz, 1080p, 1080i, 720p, 576p, 576i, 480p, 480i
Color Space	RGB / YPbPr 4:4:4, YPbPr 4:2:2/4:2:0, YUV 4:4:4
Color Depth	8/10/12-bit (1080p@60Hz, 4K@30Hz, 4K@60Hz YPbPr 4:2:2/4:2:0) 8-bit (4K@60Hz 4:4:4)
HDMI Audio Formats	LPCM 2.0/2.1/5.1/6.1/7.1, Dolby Digital, Dolby TrueHD, Dolby Digital Plus (DD+), DTS-ES, DTS HD Master, DTS HD-HRA, DTS-X
Resolution / Distance	<p>4K60:</p> <ul style="list-style-type: none"> • Cat5e: 164ft (50m) • Cat6/6a/7: 197ft (60m) • HDMI: 10ft (3m) <p>4K30 / 1080p:</p> <ul style="list-style-type: none"> • Cat5e: 164ft (50m) • Cat6/6a/7: 230ft (70m) • HDMI: 15ft (4.5m) <p>NOTE: Premium High Speed HDMI cable is highly recommended.</p>

EX-LYNX-WP-TX	
Video Input	1x HDMI Type-A (19-pin Female)
Video Outputs	1x RJ45 <i>[video send to receiver]</i>
Control Inputs/Outputs	1x Phoenix <i>[IR OUT]</i> 1x Phoenix <i>[IR IN]</i> 1x Phoenix <i>[RS-232 pass-through]</i>
Service	1x Micro USB
Power	1x DC 12V/1A (not included)
Dimensions	1-gang plate, 38.1mm D (1.50") (from back of plate to rear)
Weight	159g (0.35 lbs.)